

ETC-2 for SSTE

Installation Instructions

Warning! This Tape cartridge is specifically designed to be used on the Fulltone SSTE and will not operate correctly on a TTE or any Echoplex.

Improper installation of this tape cartridge and failure to keep the tape path and heads clean may result in the cart jamming, which will void the warranty. It is strongly recommended that you watch the **“Tape Cart installation Video”** at Fulltone’s YouTube page <http://www.youtube.com/fulltoneeffects> or directly at <https://youtu.be/bneOmDsJwtQ> prior to attempting installation cart and during the installation.

After installation, **leave the metal Tape cover OFF the machine for an hour or so to monitor the tape’s behavior** inside the cart. The tape should run smoothly, with the upper and lower bands of tape staying together in a group, and no lone strands of tape lifting up in a wave-like manner. Again, refer to the youtube video for an example of proper tape behavior.


Limited Warranty: Fulltone guarantees the ETC-2 tape cart to run for 3 months from date of installation under the following conditions only:

- 1) You must prove the cart was properly installed on a clean, well-maintained Fulltone SSTE by making a clear, close-up video of the Tape cart running after the install. Keep this video on file in case of any problems. This video will help us diagnose any other problems as well.
- 2) The cart must not have been damaged due to user-error. We will make the determination as to what constitutes “user-error.”
- 3) If you have any problems with your tape, contact Tech Dept at engineer@fulltone.com

Remember! It’s up to you to keep your tape machine clean. Don’t contact us with complaints of weak Echo or Noise until AFTER you’ve cleaned and demagnetized the heads and tape path in the correct manner as described in you SSTE manual.

See page 2 for how to properly install your “Copper Tape Cleaning arm.”

ETC-2 (SSTE) Copper/Felt Arm



Install like this for SSTE

